

RT332 /Product Specifications

Basic parameters

Product model RT332 barcode scanner: < 145g (excluding wire); Charge Stande < 105g (excluding wire)、

Scanner size 175mm (L) * 55mm (W) * 86mm (H)

standsize 130mm (L) * 100mm (W) * 100mm (H)

Material ABS plastic

Performance parameter

Connection method	Wired, 2.4G wireless, Bluetooth	Bit error rate	1/500 million
Wireless communication mode	Synchronization mode, storage mode	Storage	16MB / Save 130,000 barcodes
Wireless standard	2.4GHz	Offline storage	130,000 barcodes
Transmission distance	200 meter(Open area)	Interface	USB (1.5m cable)
battery capacity	2000mAh	Anti-drop performance	1.5m free fall
Charging time	4 hours	Prompt method	Buzzer, indicator light
Continuous working time	≥10hours or Continuous scanning about 40,000 times	Operating Voltage	DC 5V
Depth of field	≥4mil, 20mm - 380mm	Operating temperature	-20*0 - 50°C

Readable barcode type

1D: UPC-A, UPC-E, EAN-8, EAN-13, Code 128, Code 39, Code 93, Code 11

Interleaved 2 of 5, Matrix 2 of 5, Standard 2 of 5 (IATA) , Codabar (NW-7) MSI Plessey, RSS, etc.

2D: QR Code, Data Matrix, PDF417, Aztec code, MicroPDF417,Chinese, etc.